

TECHNICAL DATA SHEET

G & F Products

STYLE
3100-10

G & F Products - 3100-10 120 Pairs Large Rubber Latex Double Coated Work Gloves for Construction, gardening gloves, heavy duty Cotton Blend Blue

**1. DESCRIPTION**

Product description	Cotton and nylon blend string knit glove with a double-layer natural rubber latex coating and textured crinkle finish over the palm and fingers. Breathable knit back and knit wrist.
Intended applications	Construction, landscaping, warehouse and material handling, gardening, fencing, demolition, light hauling, mechanical repairs, equipment assembly, shipping and receiving.

2. FEATURES AND BENEFITS

- Double-layer latex coating for extended wear life over single-dip gloves
- Textured crinkle finish maintains grip on wet and lightly oiled surfaces
- Cotton blend liner is breathable for long shifts
- Knit wrist keeps debris out without restricting movement
- Sold by the dozen and by the case

3. INDUSTRIES AND APPLICATIONS

Industries	Construction / landscaping and grounds / warehousing and distribution / general manufacturing / agriculture
Typical tasks	Material handling, fencing, demolition clean-up, planting and pruning, box and pallet handling, equipment assembly

4. TECHNICAL DATA

Manufacturer item number	3100-10
UPC (GTIN-12)	899324001318
Liner / shell material	Cotton string knit
Coating material	Natural rubber latex, double layer
Coating coverage	Palm and fingers; recorded as Double Dipped for 1511-10 rows
Coating colour	Blue
Grip / finish	Textured crinkle
Cuff	Knit wrist
Construction	Seamless string knit, dipped
Colour(s)	Blue coating, natural knit back
Sizes available	Small, Medium, Large, X-Large
Sizing basis	Hand circumference below the knuckles, thumb excluded: S 7.5-8.5 in / M 8.5-9 in / L 9-9.5 in / XL 9.5-10 in
Unit of measure	Pair
Packaging	12 pairs per dozen pack / 120 pairs per case pack
Country of origin	China

5. PERFORMANCE DATA

Standard and edition	Property	Result	Test method	Laboratory	Report no. / date
EN 388:2016+A1:2018	Rating string	2131	EN 388	CTC Shanghai	SH60346-14, 7 Mar 2014
EN 388	Abrasion resistance	Level 2	—	CTC Shanghai	S200200689_1, 19 Feb 2020
EN 388	Blade cut resistance	Level 1	—	CTC Shanghai	SH60346-14
EN 388	Tear resistance	Level 3	—	CTC Shanghai	SH60346-14
EN 388	Puncture resistance	Level 1	—	CTC Shanghai	SH60346-14
EN 420 / EN ISO 21420	Dexterity	Level 5	—	CTC Shanghai	SH60346-14

6. CARE AND SERVICE LIFE

Inspection before use	Inspect for holes, tears, coating separation or stiffening before each use.
Critical defects - discard immediately	Any hole, tear or cut through the material; coating separated from the shell.
Major defects - remove from service	Material hardened, cracked or worn smooth; seam or cuff separation.
Storage conditions	Store clean and dry, away from direct sunlight, heat and ozone sources.

7. REGULATORY AND MATERIAL STATEMENTS

Natural rubber latex	CONTAINS NATURAL RUBBER LATEX. May cause an allergic reaction in sensitised individuals.
CPSIA	Not applicable - adult product
Food contact	Not claimed
Chrome VI	Not applicable

8. SKU INFORMATION

SKU	Size	Colour	Pack	UPC
3100-DZ	S / M / L / XL	Blue	12 pairs	899324003343
3100-10	S / M / L / XL	Blue	120 pairs	899324001318
1511M-DZ	Medium	Blue	12 pairs	899324000182
1511L-DZ	Large	Blue	12 pairs	899324001004
1511S-10	Small	Blue	120 pairs	818917022073
1511XL-10	X-Large	Blue	120 pairs	818917022066

DISCLAIMER

The information in this data sheet is provided in good faith and is believed accurate at the date of issue. Neither this document nor any statement made in it should be construed as a warranty of merchantability or that any product is fit for a particular purpose. The user is responsible for assessing the hazards of the intended application, for selecting appropriate protective equipment, and for conducting any testing needed to confirm suitability. Performance ratings apply to the product as supplied and unmodified. Specifications are subject to change.

DOCUMENT CONTROL

Document no.	Revision	Issue date	Originator	Revised by	Revision date
TDS-B007RFIL9I	1.0	—	—	—	—